



US006493034B1

(12) **United States Patent**
Elberbaum

(10) **Patent No.:** **US 6,493,034 B1**
(45) **Date of Patent:** **Dec. 10, 2002**

(54) **METHOD AND APPARATUS FOR REMOTE ADJUSTMENT OF A TIME DELAY CIRCUIT OF EXTERNALLY SYNCHRONIZED VIDEO TRANSMITTERS**

(75) **Inventor:** David Elberbaum, Tokyo (JP)

(73) **Assignee:** Elbex Video Ltd., Tokyo (JP)

(*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** 09/378,903

(22) **Filed:** Aug. 23, 1999

(51) **Int. Cl.⁷** H04N 9/475

(52) **U.S. Cl.** 348/512; 348/518; 348/705;
370/519; 375/358

(58) **Field of Search** 348/512, 513,
348/518, 519, 705; 370/503, 507, 508,
519, 520; 375/355, 358, 362; H04N 9/475

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,603,352 A * 7/1986 Kaneta et al. 348/518
5,249,051 A * 9/1993 Elberbaum et al. 348/521
5,283,649 A * 2/1994 Elderbaum et al. 348/500
5,293,231 A * 3/1994 Elberbaum et al. 348/500

5,303,050 A * 4/1994 Nishimura et al. 348/211.2
5,335,014 A * 8/1994 Elberbaum 348/159
5,579,060 A * 11/1996 Elberbaum 348/705
5,751,368 A * 5/1998 Cooper 348/129
5,995,140 A * 11/1999 Cooper et al. 348/153
6,005,633 A * 12/1999 Kosugi 348/14.02

* cited by examiner

Primary Examiner—John Miller

Assistant Examiner—Brian Yenke

(74) *Attorney, Agent, or Firm*—Katten Muchin Zavis
Rosenman

(57) **ABSTRACT**

In a method and apparatus for delaying propagation time of an external synchronizing signal transmitted from a receiver to transmitters which transmit a video signal to the receiver, each transmitter has an adjustable propagation delay timer which delays propagation of the external synchronizing signal. The receiver includes a detection circuit for detecting a time coincidence or a time difference between the external synchronizing signal and a sync portion of a video signal selected by a selector to be transmitted to the receiver, and a circuit which modifies the external synchronizing signal to produce a fluctuated external synchronizing signal when the detection circuit detects the time difference between the external synchronizing signal and the sync portion of the selected video signal.

31 Claims, 10 Drawing Sheets

